


Ultra-Fast Recovery Rectifier Diodes



Features

- High frequency operation
- High surge forward current capability
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Adopt GPP chip
- Passivation for enhanced ruggedness and long term reliability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

Typical applications are in switching power supplies, converters, freewheeling diodes, and reverse battery protection.

Mechanical Data

- **Package:** TO-220AC
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked

■Maximum Ratings (T_a=25°C Unless otherwise specified)

| PARAMETER | SYMBOL | UNIT | MUR1610-B1-0000S | MUR1615-B1-0000S | MUR1620-B1-0000S |
|--|------------------|------------------|------------------|------------------|------------------|
| Device Marking Code | | | MUR1610 | MUR1615 | MUR1620 |
| Repetitive Peak Reverse Voltage | VRRM | V | 100 | 150 | 200 |
| Average Rectified Output Current @60Hz half sine-wave, R-load, T _c (FIG.1) | I _o | A | 16 | | |
| Surge(Non-repetitive)Forward Current @60Hz half sine-wave, 1 cycle, T _a =25°C | IFSM | A | 150 | | |
| Current Squared Time @1ms≤t<8.3ms T _j =25°C | I ² t | A ² s | 94 | | |
| Storage Temperature | T _{stg} | °C | -55 ~ +150 | | |
| Junction Temperature | T _j | °C | -55 ~ +150 | | |

■Electrical Characteristics (T_a=25°C Unless otherwise specified)

| PARAMETER | SYMBOL | UNIT | TEST CONDITIONS | MUR1610-B1-0000S | MUR1615-B1-0000S | MUR1620-B1-0000S |
|---|-------------------|------|--|---------------------|------------------|------------------|
| Maximum instantaneous forward voltage drop per diode | VFM | V | I _{FM} =16.0A | 0.975 | | |
| Maximum DC reverse current at rated DC blocking voltage per diode | I _{RRM1} | uA | V _{RM} =V _{RRM} T _a =25°C | 10 | | |
| | I _{RRM2} | | V _{RM} =V _{RRM} T _a =125°C | 500 | | |
| Reverse Recovery Time | T _{rr} | ns | I _F =0.5A I _{RR} =0.25A | I _{RM} =1A | 50 | |

■Thermal Characteristics (T_a=25°C Unless otherwise specified)

| PARAMETER | SYMBOL | UNIT | MUR1610-B1-0000S | MUR1615-B1-0000S | MUR1620-B1-0000S |
|---|-------------------|------|------------------|------------------|------------------|
| Thermal Resistance Between junction and case | R _{θJ-C} | °C/W | 2.0 | | |



MUR1610 THRU MUR1620-B1-0000S

Ordering Information (Example)

| PREFERRED P/N | | | UNIT WEIGHT(g) | MINIMUM PACKAGE(pcs) | INNER BOX QUANTITY(pcs) | OUTER CARTON QUANTITY(pcs) | DELIVERY MODE |
|------------------|------------------|------------------|------------------|----------------------|-------------------------|----------------------------|---------------|
| MUR1610-B1-0000S | MUR1615-B1-0000S | MUR1620-B1-0000S | Approximate 1.87 | 50 | 1000 | 5000 | Tube |

Characteristics (Typical)









FIG.5 Diagram of circuit and Testing wave form of reverse recovery time



■ Outline Dimensions



| TO-220AC | | |
|----------|-------|-------|
| Dim | Min | Max |
| A | 9.5 | 10.9 |
| B | 2.22 | 3.27 |
| C | 3.34 | 4.31 |
| D | 14.5 | 15.5 |
| E | 3.16 | 4.46 |
| F | 0.28 | 0.64 |
| G | 0.68 | 0.94 |
| H | 13.06 | 14.62 |
| I | 4.55 | 5.60 |
| J | 4.04 | 5.1 |
| K | 1.14 | 1.4 |
| L | 2.14 | 3.19 |



MUR1610 THRU MUR1620-B1-0000S

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.